



SPH120

SIMAG

	FEATURES • Resistant stainless steel exterior. • Direct trasmission • Low power and water consumption • Easy, front panel access to technical / service area of the machine. • Electronic control board with self diagnostic and malfunction alarms. • Continuous production • Reduced dimensions																	
	CONDENSING SYSTEM Air cooled Water cooled	 Factory 12 sandown Square 56 Smith Rd Springvale Victoria																
	REFRIGERANT GAS R290																	
	VOLTAGE V/HZ/PH 230\50\1																	
CERTIFICATIONS   	OPERATING REQUIREMENTS <table><tr><td></td><td>Minimum</td><td>Maximum</td></tr><tr><td>Air temperature</td><td>10</td><td>43</td></tr><tr><td>Water temperature</td><td>5</td><td>38</td></tr><tr><td>Water pressure</td><td>1 bar (14 psi)</td><td>5 bar (70 psi)</td></tr><tr><td>Electrical voltage</td><td>-10%</td><td>+10%</td></tr></table>				Minimum	Maximum	Air temperature	10	43	Water temperature	5	38	Water pressure	1 bar (14 psi)	5 bar (70 psi)	Electrical voltage	-10%	+10%
	Minimum	Maximum																
Air temperature	10	43																
Water temperature	5	38																
Water pressure	1 bar (14 psi)	5 bar (70 psi)																
Electrical voltage	-10%	+10%																

