



SDH40

SIMAG

Technical features

- Stainless steel bodywork - scotch brite
- Vertical pump
- Built-in cleaning system
- Easily accessible components
- Low power and water consumption
- Optimum ratio between ice production and bin capacity
- Reduced dimensions
- Double defrosting system
- Refrigerant R290




Internal bin capacity



12 kg of ice
570 cubes

Type of ice

Hollow Cubes



Voltage

230/50/1 Standard version

Machine dimensions

Net size WxDxH	377 x 555 x 726 mm
Net weight	40 kg
Shipping size WxDxH	450 x 620 x 740 mm
Shipping weight	47 kg

Technology and Certifications




**Factory 12, Sandown Square
56 Smith Rd
Springvale Vic 3171**



SDH40

SIMAG



Operating Limits

	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar	5 bar
Electrical voltage	-10 %	+10 %

Specifications and design are subject to change without notice

Model	Voltage	Daily production kg		Power input Watt (*)	Refrigerant		Fuse A	Consumptions (**)		
		10°C/10°C	21°C/10°C		Type	Charge kg		kWh/ 100kg	kWh/ 24h	Water l/h
SDH40	230/50/1	41	33.5	300	R290	0.120	10	22.5	5.7	3.9

(**) Water Consumption: at 32°C Air and 21°C Water

(*) Power Input: at 43°C Ambient Temperature